0.1: Physical Constants

Speed of light	c	$3 \times 10^8 \text{ m/s}$		
Planck constant	h	$6.63 \times 10^{-34} \text{ J s}$		
	hc	1242 eV-nm		
Gravitation constant	G	$6.67 \times 10^{-11} \text{ m}^3 \text{ kg}^{-1} \text{ s}^{-2}$		
Boltzmann constant	k	$1.38 \times 10^{-23} \text{ J/K}$		
Molar gas constant	R	8.314 J/(mol K)		
Avogadro's number	$N_{\rm A}$	$6.023 \times 10^{23} \text{ mol}^{-1}$		
Charge of electron	e	$1.602 \times 10^{-19} \text{ C}$		
Permeability of vac-	μ_0	$4\pi \times 10^{-7} \text{ N/A}^2$		
uum				
Permitivity of vacuum	ϵ_0	$8.85 \times 10^{-12} \text{ F/m}$		
Coulomb constant	$\frac{1}{4\pi\epsilon_0}$	$9 \times 10^9 \text{ N m}^2/\text{C}^2$		
Faraday constant	F	96485 C/mol		
Mass of electron	m_e	$9.1 \times 10^{-31} \text{ kg}$		
Mass of proton	m_p	$1.6726 \times 10^{-27} \text{ kg}$		
Mass of neutron	m_n	$1.6749 \times 10^{-27} \text{ kg}$		
Atomic mass unit	u	$1.66 \times 10^{-27} \text{ kg}$		
Atomic mass unit	u	$931.49 { m MeV/c^2}$		
Stefan-Boltzmann	σ	$5.67 \times 10^{-8} \text{ W/(m}^2 \text{ K}^4)$		
constant				
Rydberg constant	R_{∞}	$1.097 \times 10^7 \text{ m}^{-1}$		
Bohr magneton	μ_B	$9.27 \times 10^{-24} \text{ J/T}$		
Bohr radius	a_0	0.529×10^{-10} m		
Standard atmosphere	atm	$1.01325 \times 10^5 \text{ Pa}$		
Wien displacement	b	$2.9 \times 10^{-3} \mathrm{m K}$		
constant				

1 MECHANICS

1.1: Vectors

Notation: $\vec{a} = a_x \hat{\imath} + a_y \hat{\jmath} + a_z \hat{k}$

Magnitude: $a = |\vec{a}| = \sqrt{a_x^2 + a_y^2 + a_z^2}$

Dot product: $\vec{a} \cdot \vec{b} = a_x b_x + a_y b_y + a_z b_z = ab \cos \theta$

Cross product:



$$\begin{split} \vec{a}\times\vec{b} &= (a_yb_z-a_zb_y)\hat{\imath} + (a_zb_x-a_xb_z)\hat{\jmath} + (a_xb_y-a_yb_x)\hat{k} \\ &|\vec{a}\times\vec{b}| = ab\sin\theta \end{split}$$

1.2: Kinematics

Average and Instantaneous Vel. and Accel.:

$\vec{v}_{\rm av} = \Delta \vec{r} / \Delta t,$	$\vec{v}_{\rm inst} = d\vec{r}/dt$
$\vec{a}_{\rm av} = \Delta \vec{v} / \Delta t$	$\vec{a}_{\rm inst} = d\vec{v}/dt$

Motion in a straight line with constant *a*:

$$v = u + at$$
, $s = ut + \frac{1}{2}at^2$, $v^2 - u^2 = 2as$

Relative Velocity: $\vec{v}_{A/B} = \vec{v}_A - \vec{v}_B$

Projectile Motion:

$$\begin{aligned} x &= ut\cos\theta, \quad y = ut\sin\theta - \frac{1}{2}gt^2\\ y &= x\tan\theta - \frac{g}{2u^2\cos^2\theta}x^2\\ T &= \frac{2u\sin\theta}{g}, \quad R = \frac{u^2\sin2\theta}{g}, \quad H = \frac{u^2\sin^2\theta}{2g} \end{aligned}$$

1.3: Newton's Laws and Friction

Linear momentum: $\vec{p} = m\vec{v}$ Newton's first law: inertial frame. Newton's second law: $\vec{F} = \frac{d\vec{p}}{dt}$, $\vec{F} = m\vec{a}$ Newton's third law: $\vec{F}_{AB} = -\vec{F}_{BA}$ Frictional force: $f_{\text{static, max}} = \mu_s N$, $f_{\text{kinetic}} = \mu_k N$ Banking angle: $\frac{v^2}{rg} = \tan \theta$, $\frac{v^2}{rg} = \frac{\mu + \tan \theta}{1 - \mu \tan \theta}$ Centripetal force: $F_c = \frac{mv^2}{r}$, $a_c = \frac{v^2}{r}$ Pseudo force: $\vec{F}_{\text{pseudo}} = -m\vec{a}_0$, $F_{\text{centrifugal}} = -\frac{mv^2}{r}$ Minimum speed to complete vertical circle: $v_{\text{min, bottom}} = \sqrt{5gl}$, $v_{\text{min, top}} = \sqrt{gl}$

Conical pendulum: $T = 2\pi \sqrt{\frac{l\cos\theta}{g}}$



1.4: Work, Power and Energy Work: $W = \vec{F} \cdot \vec{S} = FS \cos \theta$, $W = \int \vec{F} \cdot d\vec{S}$ Kinetic energy: $K = \frac{1}{2}mv^2 = \frac{p^2}{2m}$

Potential energy: $F = -\partial U / \partial x$ for conservative forces.

$$U_{\text{gravitational}} = mgh, \quad U_{\text{spring}} = \frac{1}{2}kx^2$$

Work done by conservative forces is path independent and depends only on initial and final points: $\oint \vec{F}_{\text{conservative}} \cdot d\vec{r} = 0.$

Work-energy theorem: $W = \Delta K$

Mechanical energy: E = U + K. Conserved if forces are conservative in nature.

Power
$$P_{\rm av} = \frac{\Delta W}{\Delta t}, \quad P_{\rm inst} = \vec{F} \cdot \vec{v}$$

1.5: Centre of Mass and Collision	
Centre of mass: $x_{cm} = \frac{\sum x_i m_i}{\sum m_i}, x_{cm}$	$= rac{\int x \mathrm{d}m}{\int \mathrm{d}m}$
CM of few useful configurations:	

- 1. m_1, m_2 separated by r:
- 2. Triangle (CM \equiv Centroid) $y_c = \frac{h}{3}$
- 3. Semicircular ring: $y_c = \frac{2r}{\pi}$
- 4. Semicircular disc: $y_c = \frac{4r}{3\pi}$
- 5. Hemispherical shell: $y_c = \frac{r}{2}$
- 6. Solid Hemisphere: $y_c = \frac{3r}{8}$
- 7. Cone: the height of CM from the base is h/4 for the solid cone and h/3 for the hollow cone.

Motion of the CM: $M = \sum m_i$

$$\vec{v}_{\rm cm} = \frac{\sum m_i \vec{v}_i}{M}, \quad \vec{p}_{\rm cm} = M \vec{v}_{\rm cm}, \quad \vec{a}_{\rm cm} = \frac{\vec{F}_{\rm ext}}{M}$$

Impulse: $\vec{J} = \int \vec{F} \, dt = \Delta \vec{p}$

Collision:

 $\begin{array}{c} m_1 \\ \rightarrow v_1' \end{array} \xrightarrow{m_2}$

Before collision After collision

 m_2

 $\rightarrow v_2$

 $\frac{m_2r}{m_1+m_2}$

 $\frac{m_1r}{m_1+m_2}$

Momentum conservation: $m_1v_1 + m_2v_2 = m_1v'_1 + m_2v'_2$ Elastic Collision: $\frac{1}{2}m_1v_1^2 + \frac{1}{2}m_2v_2^2 = \frac{1}{2}m_1v'_1^2 + \frac{1}{2}m_2v'_2^2$ Coefficient of restitution:

 $\rightarrow v_1$

$$e = \frac{-(v_1' - v_2')}{v_1 - v_2} = \begin{cases} 1, & \text{completely elastic} \\ 0, & \text{completely in-elastic} \end{cases}$$

If $v_2 = 0$ and $m_1 \ll m_2$ then $v'_1 = -v_1$. If $v_2 = 0$ and $m_1 \gg m_2$ then $v'_2 = 2v_1$. Elastic collision with $m_1 = m_2$: $v'_1 = v_2$ and $v'_2 = v_1$.

1.6: Rigid Body Dynamics

Angular velocity: $\omega_{av} = \frac{\Delta \theta}{\Delta t}, \quad \omega = \frac{d\theta}{dt}, \quad \vec{v} = \vec{\omega} \times \vec{r}$ **Angular Accel.:** $\alpha_{av} = \frac{\Delta \omega}{\Delta t}, \quad \alpha = \frac{d\omega}{dt}, \quad \vec{a} = \vec{\alpha} \times \vec{r}$

Rotation about an axis with constant α :

 $\omega = \omega_0 + \alpha t, \quad \theta = \omega t + \frac{1}{2}\alpha t^2, \quad \omega^2 - \omega_0^2 = 2\alpha\theta$

Moment of Inertia: $I = \sum_{i} m_i r_i^2$, $I = \int r^2 dm$

www.concepts-of-physics.com



Theorem of Parallel Axes: $I_{\parallel} = I_{cm} + md^2$

Theorem of Perp. Axes:
$$I_z = I_x + I_y$$

$$z y$$

 $x \rightarrow x$

Radius of Gyration: $k = \sqrt{I/m}$

Angular Momentum: $\vec{L} = \vec{r} \times \vec{p}, \quad \vec{L} = I\vec{\omega}$

Torque: $\vec{\tau} = \vec{r} \times \vec{F}$, $\vec{\tau} = \frac{\mathrm{d}\vec{L}}{\mathrm{d}t}$, $\tau = I\alpha$

Conservation of \vec{L} : $\vec{\tau}_{ext} = 0 \implies \vec{L} = const.$ Equilibrium condition: $\sum \vec{F} = \vec{0}, \quad \sum \vec{\tau} = \vec{0}$ Kinetic Energy: $K_{rot} = \frac{1}{2}I\omega^2$

Dynamics:

$$\begin{split} \vec{\tau}_{\rm cm} &= I_{\rm cm} \vec{\alpha}, \qquad \vec{F}_{\rm ext} = m \vec{a}_{\rm cm}, \qquad \vec{p}_{\rm cm} = m \vec{v}_{\rm cm} \\ K &= \frac{1}{2} m v_{\rm cm}^2 + \frac{1}{2} I_{\rm cm} \omega^2, \quad \vec{L} = I_{\rm cm} \vec{\omega} + \vec{r}_{\rm cm} \times m \vec{v}_{\rm cm} \end{split}$$

1.7: Gravitation

Gravitational force: $F = G \frac{m_1 m_2}{r^2}$ Potential energy: $U = -\frac{GMm}{r}$ Gravitational acceleration: $g = \frac{GM}{R^2}$ Variation of g with depth: $g_{\text{inside}} \approx g \left(1 - \frac{2h}{R}\right)$ Variation of g with height: $g_{\text{outside}} \approx g \left(1 - \frac{h}{R}\right)$ Effect of non-spherical earth shape on g: $g_{\text{at pole}} > g_{\text{at equator}}$ ($\because R_{\text{e}} - R_{\text{p}} \approx 21 \text{ km}$)

Effect of earth rotation on apparent weight:

$$mg'_{\theta} = mg - m\omega^2 R \cos^2 \theta$$

 $mg'_{\theta} = mg - m\omega^2 R \cos^2 \theta$

Orbital velocity of satellite: $v_o = \sqrt{\frac{GM}{R}}$

Escape velocity: $v_e = \sqrt{\frac{2GM}{R}}$

Kepler's laws:



First: Elliptical orbit with sun at one of the focus. **Second:** Areal velocity is constant. ($\because d\vec{L}/dt = 0$). **Third:** $T^2 \propto a^3$. In circular orbit $T^2 = \frac{4\pi^2}{GM}a^3$.

1.8: Simple Harmonic Motion

Hooke's law: F = -kx (for small elongation x.) Acceleration: $a = \frac{d^2x}{dt^2} = -\frac{k}{m}x = -\omega^2 x$ Time period: $T = \frac{2\pi}{\omega} = 2\pi\sqrt{\frac{m}{k}}$ Displacement: $x = A\sin(\omega t + \phi)$ Velocity: $v = A\omega\cos(\omega t + \phi) = \pm\omega\sqrt{A^2 - x^2}$

Potential energy: $U = \frac{1}{2}kx^2$

Kinetic energy $K = \frac{1}{2}mv^2$

$$-A \xrightarrow{0} A x$$

Total energy: $E = U + K = \frac{1}{2}m\omega^2 A^2$

Simple pendulum: $T = 2\pi \sqrt{\frac{l}{g}}$

Physical Pendulum: $T = 2\pi \sqrt{\frac{I}{mgl}}$

Torsional Pendulum $T = 2\pi \sqrt{\frac{I}{k}}$

Springs in series: $\frac{1}{k_{eq}} = \frac{1}{k_1} + \frac{1}{k_2}$ Springs in parallel: $k_{eq} = k_1 + k_2$

Superposition of two SHM's:

$$\begin{array}{c}
\vec{A} \\
\vec{A_2} \\
\vec{A_2} \\
\vec{A_1} \\
\vec{A_1}
\end{array}$$

 $k_1 \quad k_2$

 $\lim_{k_1} k_2 \atop k_1$

0

$$x_1 = A_1 \sin \omega t, \qquad x_2 = A_2 \sin(\omega t + \delta)$$
$$x = x_1 + x_2 = A \sin(\omega t + \epsilon)$$
$$A = \sqrt{A_1^2 + A_2^2 + 2A_1 A_2 \cos \delta}$$
$$\tan \epsilon = \frac{A_2 \sin \delta}{A_1 + A_2 \cos \delta}$$

1.9: Properties of Matter

Modulus of rigidity: $Y = \frac{F/A}{\Delta l/l}$, $B = -V \frac{\Delta P}{\Delta V}$, $\eta = \frac{F}{A\theta}$ Compressibility: $K = \frac{1}{B} = -\frac{1}{V} \frac{dV}{dP}$ Poisson's ratio: $\sigma = \frac{\text{lateral strain}}{\text{longitudinal strain}} = \frac{\Delta D/D}{\Delta l/l}$ Elastic energy: $U = \frac{1}{2}$ stress × strain × volume

Surface tension:
$$S = F/l$$

Surface energy: $U = SA$
Excess pressure in hubble:

$$\Delta p_{\rm air} = 2S/R, \quad \Delta p_{\rm soap} = 4S/R$$

Capillary rise: $h = \frac{2S\cos\theta}{r\rho g}$

Hydrostatic pressure: $p = \rho gh$ Buoyant force: $F_B = \rho Vg$ = Weight of displaced liquid Equation of continuity: $A_1v_1 = A_2v_2$ $v_1 \leftarrow 0$ Bernoulli's equation: $p + \frac{1}{2}\rho v^2 + \rho gh$ = constant Torricelli's theorem: $v_{\text{efflux}} = \sqrt{2gh}$ Viscous force: $F = -\eta A \frac{dv}{dx}$

Stoke's law:
$$F = 6\pi\eta rv$$

Poiseuilli's equation: $\frac{\text{Volume flow}}{\text{time}} = \frac{\pi p r^4}{8\eta l}$

 $\Rightarrow 0^r$

Terminal velocity: $v_t = \frac{2r^2(\rho-\sigma)g}{9\eta}$



Visit www.concepts-of-physics.com to buy "IIT JEE Physics (1978-2016: 39 Year) Topic-wise Complete Solutions". Foreword by Prof HC Verma.

Formulae Sheet for Physics

www.concepts-of-physics.com

2 Waves

2.1: Waves Motion

General equation of wave: $\frac{\partial^2 y}{\partial x^2} = \frac{1}{v^2} \frac{\partial^2 y}{\partial t^2}$.

Notation: Amplitude A, Frequency ν , Wavelength λ , Period T, Angular Frequency ω , Wave Number k,

$$T = \frac{1}{\nu} = \frac{2\pi}{\omega}, \quad v = \nu\lambda, \quad k = \frac{2\pi}{\lambda}$$

Progressive wave travelling with speed v:

$$y = f(t - x/v), \rightsquigarrow +x; \quad y = f(t + x/v), \rightsquigarrow -x$$



Progressive sine wave:

$$y = A\sin(kx - \omega t) = A\sin(2\pi \left(x/\lambda - t/T\right))$$

2.2: Waves on a String

Speed of waves on a string with mass per unit length μ and tension T: $v = \sqrt{T/\mu}$

Transmitted power: $P_{\rm av} = 2\pi^2 \mu v A^2 \nu^2$

Interference:

$$y_1 = A_1 \sin(kx - \omega t), \quad y_2 = A_2 \sin(kx - \omega t + \delta)$$

$$y = y_1 + y_2 = A \sin(kx - \omega t + \epsilon)$$

$$A = \sqrt{A_1^2 + A_2^2 + 2A_1A_2 \cos \delta}$$

$$\tan \epsilon = \frac{A_2 \sin \delta}{A_1 + A_2 \cos \delta}$$

$$\delta = \begin{cases} 2n\pi, & \text{constructive;} \\ (2n+1)\pi, & \text{destructive.} \end{cases}$$

Standing Waves:

$$y_1 = A_1 \sin(kx - \omega t), \quad y_2 = A_2 \sin(kx + \omega t)$$
$$y = y_1 + y_2 = (2A \cos kx) \sin \omega t$$
$$x = \begin{cases} (n + \frac{1}{2}) \frac{\lambda}{2}, & \text{nodes;} \quad n = 0, 1, 2, \dots \\ n\frac{\lambda}{2}, & \text{antinodes.} \quad n = 0, 1, 2, \dots \end{cases}$$

String fixed at both ends:

$$N \xrightarrow{L} N$$

- 1. Boundary conditions: y = 0 at x = 0 and at x = L
- 2. Allowed Freq.: $L = n\frac{\lambda}{2}, \ \nu = \frac{n}{2L}\sqrt{\frac{T}{\mu}}, \ n = 1, 2, 3, \dots$
- 3. Fundamental/1st harmonics: $\nu_0 = \frac{1}{2L} \sqrt{\frac{T}{\mu}}$

- 4. 1st overtone/2nd harmonics: $\nu_1 = \frac{2}{2L} \sqrt{\frac{T}{\mu}}$
 - '
- 5. 2nd overtone/3rd harmonics: $\nu_2 = \frac{3}{2L} \sqrt{\frac{T}{\mu}}$
- 6. All harmonics are present.

String fixed at one end:



- 1. Boundary conditions: y = 0 at x = 0
- 2. Allowed Freq.: $L = (2n+1)\frac{\lambda}{4}, \ \nu = \frac{2n+1}{4L}\sqrt{\frac{T}{\mu}}, \ n = 0, 1, 2, \dots$
- 3. Fundamental/1st harmonics: $\nu_0 = \frac{1}{4L} \sqrt{\frac{T}{\mu}}$
- 4. 1st overtone/3rd harmonics: $\nu_1 = \frac{3}{4L} \sqrt{\frac{T}{\mu}}$
- 5. 2nd overtone/5th harmonics: $\nu_2 = \frac{5}{4L} \sqrt{\frac{T}{\mu}}$
- 6. Only odd harmonics are present.

Sonometer:
$$\nu \propto \frac{1}{L}, \nu \propto \sqrt{T}, \nu \propto \frac{1}{\sqrt{\mu}}. \nu = \frac{n}{2L}\sqrt{\frac{T}{\mu}}$$

2.3: Sound Waves

Displacement wave: $s = s_0 \sin \omega (t - x/v)$

Pressure wave: $p = p_0 \cos \omega (t - x/v), \ p_0 = (B\omega/v)s_0$

Speed of sound waves:

$$v_{\text{liquid}} = \sqrt{\frac{B}{\rho}}, \quad v_{\text{solid}} = \sqrt{\frac{Y}{\rho}}, \quad v_{\text{gas}} = \sqrt{\frac{\gamma P}{\rho}}$$

Intensity: $I = \frac{2\pi^2 B}{v} s_0^2 \nu^2 = \frac{p_0^2 v}{2B} = \frac{p_0^2}{2\rho v}$

Standing longitudinal waves:

$$p_1 = p_0 \sin \omega (t - x/v), \quad p_2 = p_0 \sin \omega (t + x/v)$$
$$p = p_1 + p_2 = 2p_0 \cos kx \sin \omega t$$

Closed organ pipe:



- 1. Boundary condition: y = 0 at x = 0
- 2. Allowed freq.: $L=(2n+1)\frac{\lambda}{4},\ \nu=(2n+1)\frac{v}{4L},\ n=0,1,2,\ldots$
- 3. Fundamental/1st harmonics: $\nu_0 = \frac{v}{4L}$
- 4. 1st overtone/3rd harmonics: $\nu_1 = 3\nu_0 = \frac{3v}{4L}$

Formulae Sheet for Physics

- 5. 2nd overtone/5th harmonics: $\nu_2 = 5\nu_0 = \frac{5v}{4L}$
- 6. Only odd harmonics are present.



- 1. Boundary condition: y = 0 at x = 0Allowed freq.: $L = n\frac{\lambda}{2}, \ \nu = n\frac{v}{4L}, \ n = 1, 2, \dots$
- 2. Fundamental/1st harmonics: $\nu_0 = \frac{v}{2L}$
- 3. 1st overtone/2nd harmonics: $\nu_1 = 2\nu_0 = \frac{2v}{2L}$
- 4. 2nd overtone/3rd harmonics: $\nu_2 = 3\nu_0 = \frac{3\nu}{2L}$
- 5. All harmonics are present.





$$l_1 + d = \frac{\lambda}{2}, \quad l_2 + d = \frac{3\lambda}{4}, \quad v = 2(l_2 - l_1)\nu$$

Beats: two waves of almost equal frequencies $\omega_1 \approx \omega_2$

 $p_1 = p_0 \sin \omega_1 (t - x/v), \quad p_2 = p_0 \sin \omega_2 (t - x/v)$ $p = p_1 + p_2 = 2p_0 \cos \Delta \omega (t - x/v) \sin \omega (t - x/v)$ $\omega = (\omega_1 + \omega_2)/2, \quad \Delta \omega = \omega_1 - \omega_2 \quad \text{(beats freq.)}$

Doppler Effect:

$$\nu = \frac{v + u_o}{v - u_s} \nu_0$$

where, v is the speed of sound in the medium, u_0 is the speed of the observer w.r.t. the medium, considered positive when it moves towards the source and negative when it moves away from the source, and u_s is the speed of the source w.r.t. the medium, considered positive when it moves towards the observer and negative when it moves away from the observer.

2.4: Light Waves

Plane Wave: $E = E_0 \sin \omega (t - \frac{x}{v}), I = I_0$

Spherical Wave: $E = \frac{aE_0}{r} \sin \omega (t - \frac{r}{v}), I = \frac{I_0}{r^2}$

Young's double slit experiment

Path difference: $\Delta x = \frac{dy}{D}$



Phase difference: $\delta = \frac{2\pi}{\lambda} \Delta x$

Interference Conditions: for integer n,

$$\delta = \begin{cases} 2n\pi, & \text{constructive;} \\ (2n+1)\pi, & \text{destructive,} \end{cases}$$

$$\Delta x = \begin{cases} n\lambda, & \text{constructive;}\\ \left(n + \frac{1}{2}\right)\lambda, & \text{destructive} \end{cases}$$

Intensity:

$$I = I_1 + I_2 + 2\sqrt{I_1 I_2} \cos \delta,$$

$$I_{\max} = \left(\sqrt{I_1} + \sqrt{I_2}\right)^2, \ I_{\min} = \left(\sqrt{I_1} - \sqrt{I_2}\right)^2$$

$$I_1 = I_2 : I = 4I_0 \cos^2 \frac{\delta}{2}, \ I_{\max} = 4I_0, \ I_{\min} = 0$$

Fringe width: $w = \frac{\lambda D}{d}$ Optical path: $\Delta x' = \mu \Delta x$

Interference of waves transmitted through thin film:

$$\Delta x = 2\mu d = \begin{cases} n\lambda, & \text{constructive;} \\ \left(n + \frac{1}{2}\right)\lambda, & \text{destructive.} \end{cases}$$

Diffraction from a single slit:



For Minima: $n\lambda = b\sin\theta \approx b(y/D)$

Resolution: $\sin \theta = \frac{1.22\lambda}{h}$

Law of Malus: $I = I_0 \cos^2 \theta$





Visit www.concepts-of-physics.com to buy "IIT JEE Physics (1978-2016: 39 Year) Topic-wise Complete Solutions". Foreword by Prof HC Verma.

3 Optics

3.1: Reflection of Light

Laws of reflection:

incident i r reflected (i)

Incident ray, reflected ray, and normal lie in the same plane (ii) $\angle i = \angle r$

Plane mirror:

(i) the image and the object are equidistant from mirror (ii) virtual image of real object

Spherical Mirror:



- 1. Focal length f = R/2
- 2. Mirror equation: $\frac{1}{v} + \frac{1}{u} = \frac{1}{f}$
- 3. Magnification: $m = -\frac{v}{u}$
- u u

3.2: Refraction of Light

Refractive index:
$$\mu = \frac{\text{speed of light in vacuum}}{\text{speed of light in medium}} = \frac{c}{v}$$

Snell's Law: $\frac{\sin i}{\sin r} = \frac{\mu_2}{\mu_1}$

 $\mu_1 \qquad \mu_2 \quad \mu_2$

Apparent depth: $\mu = \frac{\text{real depth}}{\text{apparent depth}} = \frac{d}{d'}$

Critical angle: $\theta_c = \sin^{-1} \frac{1}{\mu}$



 μ_2

Deviation by a prism:

$$\begin{split} \delta &= i + i' - A, \quad \text{general result} \\ \mu &= \frac{\sin \frac{A + \delta_m}{2}}{\sin \frac{A}{2}}, \quad i = i' \text{ for minimum deviation} \end{split}$$

$$\delta_m = (\mu - 1)A$$
, for small $A = \delta_n$

$$\frac{\mu_2}{v} - \frac{\mu_1}{u} = \frac{\mu_2 - \mu_1}{R}, \quad m = \frac{\mu_1 v}{\mu_2 u}$$

Lens maker's formula: $\frac{1}{f} = (\mu - 1) \left[\frac{1}{R_1} - \frac{1}{R_2} \right]$

Lens formula:
$$\frac{1}{v} - \frac{1}{u} = \frac{1}{f}, \quad m = \frac{v}{u}$$

$$f$$

Power of the lens: $P = \frac{1}{f}$, P in diopter if f in metre. Two thin lenses separated by distance d:

$$\frac{1}{F} = \frac{1}{f_1} + \frac{1}{f_2} - \frac{d}{f_1 f_2} \qquad \qquad - \left(-\frac{1}{f_2} - \frac{1}{f_2} \right)^{-1} - \left(-\frac{1}{f$$

3.3: Optical Instruments

Simple microscope: m = D/f in normal adjustment.

Compound microscope:



- 1. Magnification in normal adjustment: $m = \frac{v}{u} \frac{D}{f_e}$
- 2. Resolving power: $R = \frac{1}{\Delta d} = \frac{2\mu \sin \theta}{\lambda}$

Astronomical telescope:

- 1. In normal adjustment: $m = -\frac{f_o}{f_e}, L = f_o + f_e$
- 2. Resolving power: $R = \frac{1}{\Delta \theta} = \frac{1}{1.22\lambda}$

3.4: Dispersion

Cauchy's equation: $\mu = \mu_0 + \frac{A}{\lambda^2}$, A > 0

Dispersion by prism with small A and i:

- 1. Mean deviation: $\delta_y = (\mu_y 1)A$
- 2. Angular dispersion: $\theta = (\mu_v \mu_r)A$

Dispersive power: $\omega = \frac{\mu_v - \mu_r}{\mu_y - 1} \approx \frac{\theta}{\delta_y}$ (if A and i small)

Dispersion without deviation:

 $(\mu_y - 1)A + (\mu'_y - 1)A' = 0$

Deviation without dispersion: $(\mu_v-\mu_r)A=(\mu_v'-\mu_r')A'$

4 Heat and Thermodynamics

4.1: Heat and Temperature

Temp. scales: $F = 32 + \frac{9}{5}C$, K = C + 273.16Ideal gas equation: pV = nRT, n: number of moles van der Waals equation: $\left(p + \frac{a}{V^2}\right)(V - b) = nRT$ Thermal expansion: $L = L_0(1 + \alpha\Delta T)$,

 $A = A_0(1 + \beta \Delta T), \quad V = V_0(1 + \gamma \Delta T), \quad \gamma = 2\beta = 3\alpha$

Thermal stress of a material: $\frac{F}{A} = Y \frac{\Delta l}{l}$

4.2: Kinetic Theory of Gases

General: $M = mN_A, k = R/N_A$

Maxwell distribution of speed:



RMS speed:
$$v_{rms} = \sqrt{\frac{3kT}{m}} = \sqrt{\frac{3RT}{M}}$$

Average speed: $\bar{v} = \sqrt{\frac{8kT}{\pi m}} = \sqrt{\frac{8RT}{\pi M}}$

Most probable speed: $v_p = \sqrt{\frac{2kT}{m}}$

Pressure: $p = \frac{1}{3}\rho v_{rms}^2$

Equipartition of energy: $K = \frac{1}{2}kT$ for each degree of freedom. Thus, $K = \frac{f}{2}kT$ for molecule having f degrees of freedoms.

Internal energy of *n* moles of an ideal gas is $U = \frac{f}{2}nRT$.

4.3: Specific Heat Specific heat: $s = \frac{Q}{m\Delta T}$ Latent heat: L = Q/mSpecific heat at constant volume: $C_v = \frac{\Delta Q}{n\Delta T}\Big|_V$ Specific heat at constant pressure: $C_p = \frac{\Delta Q}{n\Delta T}\Big|_p$ Relation between C_p and C_v : $C_p - C_v = R$ Ratio of specific heats: $\gamma = C_p/C_v$ Relation between U and C_v : $\Delta U = nC_v\Delta T$ Specific heat of gas mixture:

 $C_v = \frac{n_1 C_{v1} + n_2 C_{v2}}{n_1 + n_2}, \quad \gamma = \frac{n_1 C_{p1} + n_2 C_{p2}}{n_1 C_{v1} + n_2 C_{v2}}$

Molar internal energy of an ideal gas: $U = \frac{f}{2}RT$, f = 3 for monatomic and f = 5 for diatomic gas.

4.4: Theromodynamic Processes

First law of thermodynamics: $\Delta Q = \Delta U + \Delta W$

Work done by the gas:

$$\Delta W = p\Delta V, \quad W = \int_{V_1}^{V_2} p dV$$
$$W_{\text{isothermal}} = nRT \ln \left(\frac{V_2}{V_1}\right)$$
$$W_{\text{isobaric}} = p(V_2 - V_1)$$
$$W_{\text{adiabatic}} = \frac{p_1 V_1 - p_2 V_2}{\gamma - 1}$$
$$W_{\text{isochoric}} = 0$$

Efficiency of the heat engine:



$$\eta = \frac{\text{work done by the engine}}{\text{heat supplied to it}} = \frac{Q_1 - Q_2}{Q_1}$$
$$\eta_{\text{carnot}} = 1 - \frac{Q_2}{Q_1} = 1 - \frac{T_2}{T_1}$$

Coeff. of performance of refrigerator:

$$\begin{array}{c} T_1 \\ \uparrow Q_1 \\ \bigcirc \downarrow \downarrow Q_2 \\ \hline T_2 \end{array} W$$

$$COP = \frac{Q_2}{W} = \frac{Q_2}{Q_1 - Q_2}$$

Entropy: $\Delta S = \frac{\Delta Q}{T}, \ S_f - S_i = \int_i^f \frac{\Delta Q}{T}$

Const.
$$T: \Delta S = \frac{Q}{T}$$
, Varying $T: \Delta S = ms \ln \frac{T_f}{T_i}$

Adiabatic process: $\Delta Q = 0, \ pV^{\gamma} = \text{constant}$

4.5: Heat Transfer

Conduction: $\frac{\Delta Q}{\Delta t} = -KA\frac{\Delta T}{x}$

Thermal resistance: $R = \frac{x}{KA}$

$$R_{\text{series}} = R_1 + R_2 = \frac{1}{A} \left(\frac{x_1}{K_1} + \frac{x_2}{K_2} \right) \qquad \overbrace{K_1 \ K_2}^{K_1 \ K_2} A$$
$$\frac{1}{R_{\text{parallel}}} = \frac{1}{R_1} + \frac{1}{R_2} = \frac{1}{x} \left(K_1 A_1 + K_2 A_2 \right) \qquad \overbrace{K_1 \ K_1}^{K_2} A_1$$

Kirchhoff's Law: $\frac{\text{emissive power}}{\text{absorptive power}} = \frac{E_{\text{body}}}{a_{\text{body}}} = E_{\text{blackbody}}$

Wien's displacement law: $\lambda_m T = b$

$$\overbrace{\lambda_m}^{E_{\lambda}}$$

x

Stefan-Boltzmann law: $\frac{\Delta Q}{\Delta t} = \sigma e A T^4$ Newton's law of cooling: $\frac{dT}{dt} = -bA(T - T_0)$

5 Electricity and Magnetism

5.1: Electrostatics

Coulomb's law: $\vec{F} = \frac{1}{4\pi\epsilon_0} \frac{q_1 q_2}{r^2} \hat{r}$ Electric field: $\vec{E}(\vec{r}) = \frac{1}{4\pi\epsilon_0} \frac{q}{r^2} \hat{r}$ $\vec{q_1}$ $\vec{q_2}$ $\vec{q_1}$ $\vec{q_2}$ $\vec{q_1}$ \vec{r} $\vec{q_2}$

Electrostatic energy: $U = -\frac{1}{4\pi\epsilon_0} \frac{q_1q_2}{r}$ Electrostatic potential: $V = \frac{1}{4\pi\epsilon_0} \frac{q}{r}$

$$\mathrm{d}V = -\vec{E}\cdot\vec{r}, \quad V(\vec{r}) = -\int_{\infty}^{\vec{r}}\vec{E}\cdot\mathrm{d}\vec{r}$$

Electric dipole moment: $\vec{p} = q\vec{d}$

Potential of a dipole: $V = \frac{1}{4\pi\epsilon_0} \frac{p\cos\theta}{r^2}$ θ

Field of a dipole:

$$\vec{p}$$
 \vec{r} E_{θ}

 $-q \xrightarrow{p} +q$

 $E_r = \frac{1}{4\pi\epsilon_0} \frac{2p\cos\theta}{r^3}, \quad E_\theta = \frac{1}{4\pi\epsilon_0} \frac{p\sin\theta}{r^3}$

Torque on a dipole placed in \vec{E} : $\vec{\tau} = \vec{p} \times \vec{E}$ Pot. energy of a dipole placed in \vec{E} : $U = -\vec{p} \cdot \vec{E}$

5.2: Gauss's Law and its Applications

Electric flux: $\phi = \oint \vec{E} \cdot d\vec{S}$

Gauss's law: $\oint \vec{E} \cdot d\vec{S} = q_{\rm in}/\epsilon_0$

Field of a uniformly charged ring on its axis:

$$E_P = \frac{1}{4\pi\epsilon_0} \frac{qx}{(a^2 + x^2)^{3/2}} \qquad \qquad q \begin{pmatrix} a \\ \bullet \end{pmatrix} \xrightarrow{x \to P} \vec{E}$$

E and V of a uniformly charged sphere:

$$E = \begin{cases} \frac{1}{4\pi\epsilon_0} \frac{Qr}{R^3}, & \text{for } r < R \\ \frac{1}{4\pi\epsilon_0} \frac{Q}{r^2}, & \text{for } r \ge R \end{cases} \qquad E \qquad \qquad E \qquad \qquad P \qquad$$

${\cal E}$ and ${\cal V}$ of a uniformly charged spherical shell:

$$E = \begin{cases} 0, & \text{for } r < R \\ \frac{1}{4\pi\epsilon_0} \frac{Q}{r^2}, & \text{for } r \ge R \end{cases} \qquad E \qquad O \qquad R \\ V = \begin{cases} \frac{1}{4\pi\epsilon_0} \frac{Q}{R}, & \text{for } r < R \\ \frac{1}{4\pi\epsilon_0} \frac{Q}{r}, & \text{for } r \ge R \end{cases} \qquad V \qquad O \qquad R \\ V = \begin{cases} \frac{1}{4\pi\epsilon_0} \frac{Q}{r}, & \text{for } r \ge R \end{cases} \qquad V \qquad O \qquad R \end{cases}$$

Field of a line charge: $E = \frac{\lambda}{2\pi\epsilon_0 r}$ Field of an infinite sheet: $E = \frac{\sigma}{2\epsilon_0}$

Field in the vicinity of conducting surface: $E = \frac{\sigma}{\epsilon_0}$

5.3: Capacitors

Capacitance: C = q/V

Parallel plate capacitor: $C = \epsilon_0 A/d$

Spherical capacitor: $C = \frac{4\pi\epsilon_0 r_1 r_2}{r_2 - r_1}$

Cylindrical capacitor: $C = \frac{2\pi\epsilon_0 l}{\ln(r_2/r_1)}$

Capacitors in parallel: $C_{eq} = C_1 + C_2$

Capacitors in series: $\frac{1}{C_{eq}} = \frac{1}{C_1} + \frac{1}{C_2}$



 $A \leftarrow C_1 = C_2$

 $\left| \begin{array}{c} A \\ d \end{array} \right|_{d} A$

Force between plates of a parallel plate capacitor: $F = \frac{Q^2}{2A\epsilon_0}$

Energy stored in capacitor: $U = \frac{1}{2}CV^2 = \frac{Q^2}{2C} = \frac{1}{2}QV$ Energy density in electric field E: $U/V = \frac{1}{2}\epsilon_0 E^2$ Capacitor with dielectric: $C = \frac{\epsilon_0 KA}{d}$

5.4: Current electricity

Current density: $j = i/A = \sigma E$ Drift speed: $v_d = \frac{1}{2} \frac{eE}{m} \tau = \frac{i}{neA}$ Resistance of a wire: $R = \rho l/A$, where $\rho = 1/\sigma$ Temp. dependence of resistance: $R = R_0(1 + \alpha \Delta T)$

Ohm's law: V = iR

Kirchhoff's Laws: (i) The Junction Law: The algebraic sum of all the currents directed towards a node is zero i.e., $\Sigma_{node} I_i = 0$. (ii) The Loop Law: The algebraic sum of all the potential differences along a closed loop in a circuit is zero i.e., $\Sigma_{loop}\Delta V_i = 0$.

Resistors in parallel: $\frac{1}{R_{eq}} = \frac{1}{R_1} + \frac{1}{R_2}$

$$A \xrightarrow{R_1} R_2$$

 $A \xrightarrow{R_1 R_2} B$

Resistors in series: $R_{eq} = R_1 + R_2$

Wheatstone bridge:



Balanced if $R_1/R_2 = R_3/R_4$.

Electric Power: $P = V^2/R = I^2R = IV$

Galvanometer as an Ammeter:

$$i_g G = (i - i_g)S$$

Galvanometer as a Voltmeter:

$$V_{\rm AB} = i_g (R + G)$$

Charging of capacitors:

$$q(t) = CV \left[1 - e^{-\frac{t}{RC}} \right]$$

Discharging of capacitors: $q(t) = q_0 e^{-\frac{t}{RC}}$



Time constant in RC circuit: $\tau = RC$

Peltier effect: emf $e = \frac{\Delta H}{\Delta Q} = \frac{\text{Peltier heat}}{\text{charge transferred}}$.

Seeback effect:



- 1. Thermo-emf: $e = aT + \frac{1}{2}bT^2$
- 2. Thermoelectric power: de/dt = a + bT.
- 3. Neutral temp.: $T_n = -a/b$.
- 4. Inversion temp.: $T_i = -2a/b$.

Thomson effect: emf $e = \frac{\Delta H}{\Delta Q} = \frac{\text{Thomson heat}}{\text{charge transferred}} = \sigma \Delta T.$

Faraday's law of electrolysis: The mass deposited is

 $m = Zit = \frac{1}{F}Eit$

where i is current, t is time, Z is electrochemical equivalent, E is chemical equivalent, and F = 96485 C/g is Faraday constant.

5.5: Magnetism

Lorentz force on a moving charge: $\vec{F} = q\vec{v} \times \vec{B} + q\vec{E}$

Charged particle in a uniform magnetic field:

$$\overbrace{\vec{B}\otimes r}^{q} r = \frac{mv}{qB}, T = \frac{2\pi m}{qB}$$

Force on a current carrying wire:

iĀ

 $\vec{F}=i\;\vec{l}\times\vec{B}$

Magnetic moment of a current loop (dipole):

$$\overset{\mu}{\longleftrightarrow}\overset{A}{i} \quad \vec{\mu} =$$

Torque on a magnetic dipole placed in \vec{B} : $\vec{\tau} = \vec{\mu} \times \vec{B}$

Energy of a magnetic dipole placed in \vec{B} : $U = -\vec{\mu} \cdot \vec{B}$

Hall effect: $V_w = \frac{Bi}{ned}$

$$\overbrace{i \ \downarrow d}^{l} \overbrace{j \ \downarrow d}^{\vec{B}} \xrightarrow{\vec{B}}_{z} \xrightarrow{\gamma}_{z} \xrightarrow{\gamma}_{x}$$

5.6: Magnetic Field due to Current

Biot-Savart law:
$$d\vec{B} = \frac{\mu_0}{4\pi} \frac{i \, d\vec{l} \times \vec{r}}{r^3}$$

 θ \vec{r} \otimes \vec{B}

Field due to a straight conductor:

$$i \xrightarrow{\theta_2}{\theta_1} \otimes \vec{B}$$

 $\vec{B}_{2} \xleftarrow{d} \vec{B}_{1}$

Horizontal δ B_h

$$B = \frac{\mu_0 i}{4\pi d} (\cos \theta_1 - \cos \theta_2)$$

Field due to an infinite straight wire: $B = \frac{\mu_0 i}{2\pi d}$

Force between parallel wires: $\frac{dF}{dl} = \frac{\mu_0 i_1 i_2}{2\pi d}$

Field on the axis of a ring:

$$B_P = \frac{\mu_0 i a^2}{2(a^2 + d^2)^{3/2}}$$

Field at the centre of an arc: $B = \frac{\mu_0 i \theta}{4\pi a}$

Field at the centre of a ring: $B = \frac{\mu_0 i}{2a}$

Ampere's law: $\oint \vec{B} \cdot d\vec{l} = \mu_0 I_{\text{in}}$

Field inside a solenoid: $B = \mu_0 ni$, $n = \frac{N}{l}$

Field inside a toroid: $B = \frac{\mu_0 N i}{2\pi r}$

Field of a bar magnet:

$$B_1 = \frac{\mu_0}{4\pi} \frac{2M}{d^3}, \quad B_2 = \frac{\mu_0}{4\pi} \frac{M}{d^3}$$

Angle of dip: $B_h = B \cos \delta$

Tangent galvanometer: $B_h \tan \theta = \frac{\mu_0 n i}{2r}, \quad i = K \tan \theta$ Moving coil galvanometer: $niAB = k\theta, \quad i = \frac{k}{nAB}\theta$ Time period of magnetometer: $T = 2\pi \sqrt{\frac{I}{MB_h}}$ Permeability: $\vec{B} = \mu \vec{H}$

Formulae Sheet for Physics

www.concepts-of-physics.com

5.7: Electromagnetic Induction

Magnetic flux: $\phi = \oint \vec{B} \cdot d\vec{S}$

Faraday's law: $e = -\frac{d\phi}{dt}$

Lenz's Law: Induced current create a *B*-field that opposes the change in magnetic flux.

Motional emf: e = Blv

$$l \underbrace{\uparrow}_{-}^{+} \underbrace{\vec{v} \otimes \vec{B}}_{-}$$

Self inductance: $\phi = Li$, $e = -L\frac{\mathrm{d}i}{\mathrm{d}t}$

Self inductance of a solenoid: $L = \mu_0 n^2 (\pi r^2 l)$

Growth of current in LR circuit: $i = \frac{e}{R} \left[1 - e^{-\frac{t}{L/R}} \right]$



Decay of current in LR circuit: $i = i_0 e^{-\frac{t}{L/R}}$



Time constant of LR circuit: $\tau = L/R$

Energy stored in an inductor: $U = \frac{1}{2}Li^2$

Energy density of *B* field: $u = \frac{U}{V} = \frac{B^2}{2\mu_0}$

Mutual inductance: $\phi = Mi$, $e = -M \frac{\mathrm{d}i}{\mathrm{d}t}$

EMF induced in a rotating coil: $e = NAB\omega \sin \omega t$

Alternating current:

 $i = i_0 \sin(\omega t + \phi), \quad T = 2\pi/\omega$

Average current in AC: $\overline{i} = \frac{1}{T} \int_0^T i \, dt = 0$

RMS current:
$$i_{\rm rms} = \left[\frac{1}{T}\int_0^T i^2 \,\mathrm{d}t\right]^{1/2} = \frac{i_0}{\sqrt{2}} \quad \left[\begin{array}{c} i^2_{\rm max} \\ \hline & \hline \\ \hline & \hline \\ T \end{array}\right]^{1/2} t$$

Energy: $E = i_{\rm rms}^2 RT$

Capacitive reactance: $X_c = \frac{1}{\omega C}$

Inductive reactance: $X_L = \omega L$

Imepedance: $Z = e_0/i_0$

RC circuit:

$$\frac{1}{\omega C} \begin{pmatrix} Z \\ \phi \\ R \end{pmatrix}$$

$$Z = \sqrt{R^2 + (1/\omega C)^2}, \quad \tan \phi = \frac{1}{\omega CR}$$

LR circuit:

$$Z = \sqrt{R^2 + \omega^2 L^2}, \quad \tan \phi = \frac{\omega L}{R}$$

LCR Circuit:

$$i \underbrace{\Box}_{e_0 \sin \omega t} \underbrace{\Box}_{e_0 \sin \omega t} \underbrace{\Box}_{\omega L} \underbrace{Z}_{e_0 \sin \omega t} \underbrace{\Box}_{\omega L} \underbrace{\Box}_{R} \underbrace{\Box}_{e_0 - \omega L} \underbrace{\Box}_{e_$$

Power factor: $P = e_{rms} i_{rms} \cos \phi$

Transformer:
$$\frac{N_1}{N_2} = \frac{e_1}{e_2}, \ e_1i_1 = e_2i_2$$
 $e_1 \bigcirc N_1 \\ \downarrow \\ \downarrow \\ i_1 \\ \downarrow \\ i_2 \\ e_2$

Speed of the EM waves in vacuum: $c = 1/\sqrt{\mu_0\epsilon_0}$



Visit www.concepts-of-physics.com to buy "IIT JEE Physics (1978-2016: 39 Year) Topic-wise Complete Solutions". Foreword by Prof HC Verma.

6 Modern Physics

6.1: Photo-electric effect

Photon's energy: $E = h\nu = hc/\lambda$ Photon's momentum: $p = h/\lambda = E/c$ Max. KE of ejected photo-electron: $K_{\text{max}} = h\nu - \phi$ Threshold freq. in photo-electric effect: $\nu_0 = \phi/h$

Stopping potential: $V_o = \frac{hc}{e} \left(\frac{1}{\lambda}\right) - \frac{\phi}{e}$

de Broglie wavelength: $\lambda = h/p$

6.2: The Atom

Energy in *n*th Bohr's orbit:

$$E_n = -\frac{mZ^2e^4}{8\epsilon_0^2h^2n^2}, \quad E_n = -\frac{13.6Z^2}{n^2} \text{ eV}$$

Radius of the nth Bohr's orbit:

$$r_n = \frac{\epsilon_0 h^2 n^2}{\pi m Z e^2}, \quad r_n = \frac{n^2 a_0}{Z}, \quad a_0 = 0.529 \text{ Å}$$

Quantization of the angular momentum: $l = \frac{nh}{2\pi}$

Photon energy in state transition: $E_2 - E_1 = h\nu$

$$E_{2} \xrightarrow[h\nu]{} E_{1} \xrightarrow[h\nu]{} E_{2}$$

$$E_{1} \xrightarrow[h\nu]{} E_{1}$$

$$E_{1} \xrightarrow[h\nu]{} E_{2}$$

$$E_{2} \xrightarrow[h\nu]{} E_{2}$$

$$E_{2} \xrightarrow[h\nu]{} E_{2}$$

$$E_{2} \xrightarrow[h\nu]{} E_{2}$$

$$E_{2} \xrightarrow[h\nu]{} E_{2}$$

$$E_{1} \xrightarrow[h\nu]{} E_{2}$$

$$E_{2} \xrightarrow[h\nu]{} E_{2}$$

$$E_{1} \xrightarrow[h\nu]{} E_{2}$$

$$E_{2} \xrightarrow[h\nu]{} E_{2}$$

$$E_{1} \xrightarrow[h\nu]{} E_{2}$$

$$E_{2} \xrightarrow[h\nu]{} E_{2}$$

$$E_{3} \xrightarrow[h\nu]{} E_{2}$$

$$E_{4} \xrightarrow[h\nu]{} E_{2}$$

$$E_{2} \xrightarrow[h\nu]{} E_{2}$$

$$E_{3} \xrightarrow[h\nu]{} E_{2}$$

$$E_{4} \xrightarrow[h\nu]{} E_{2}$$

$$E_{4} \xrightarrow[h\nu]{} E_{2}$$

$$E_{4} \xrightarrow[h\nu]{} E_{2}$$

Wavelength of emitted radiation: for a transition from nth to mth state:

$$\frac{1}{\lambda} = RZ^2 \left[\frac{1}{n^2} - \frac{1}{m^2} \right]$$

X-ray spectrum: $\lambda_{\min} = \frac{hc}{eV}$



Moseley's law: $\sqrt{\nu} = a(Z-b)$

X-ray diffraction: $2d\sin\theta = n\lambda$

Heisenberg uncertainity principle: $\Delta p \Delta x \ge h/(2\pi), \qquad \Delta E \Delta t \ge h/(2\pi)$

6.3: The Nucleus

Nuclear radius:
$$R = R_0 A^{1/3}$$
, $R_0 \approx 1.1 \times 10^{-15} \text{ m}$
Decay rate: $\frac{\mathrm{d}N}{\mathrm{d}t} = -\lambda N$

Population at time t:
$$N = N_0 e^{-\lambda t}$$

$$\begin{array}{c}
N\\
N_0\\
\frac{N_0}{2}\\
O\\
t_{1/2}\\
t_{1/2}\\$$

Half life: $t_{1/2} = 0.693/\lambda$

Average life: $t_{av} = 1/\lambda$ Population after *n* half lives: $N = N_0/2^n$.

Mass defect: $\Delta m = [Zm_p + (A - Z)m_n] - M$

Binding energy:
$$B = [Zm_p + (A - Z)m_n - M]c^2$$

Q-value: $Q = U_i - U_f$

Energy released in nuclear reaction: $\Delta E = \Delta mc^2$ where $\Delta m = m_{\text{reactants}} - m_{\text{products}}$.





Amplification by a triode: $\mu = -\left.\frac{\Delta V_p}{\Delta V_g}\right|_{\Delta i_p=0}$

Relation between r_p , μ , and g_m : $\mu = r_p \times g_m$

Current in a transistor:
$$I_e = I_b + I_c$$

 α and β parameters of a transistor: $\alpha = \frac{I_c}{I_e}, \beta = \frac{I_c}{I_e}, \beta = \frac{I_c}{I_e}$

Transconductance: $g_m = \frac{\Delta I_c}{\Delta V_{be}}$

Logic Gates:

		AND	OR	NAND	NOR	XOR
Α	В	AB	A+B	\overline{AB}	$\overline{A + B}$	$A\bar{B} + \bar{A}B$
0	0	0	0	1	1	0
0	1	0	1	1	0	1
1	0	0	1	1	0	1
1	1	1	1	0	0	0

7 IIT JEE Physics Book

7.1: Book Description

Two IIT batch-mates have worked together to provide a high quality Physics problem book to Indian students. It is an indispensable collection of four decades of IIT questions and their illustrated solutions for any serious aspirant. The success of this work lies in making the readers capable to solve complex problems using few basic principles. The readers are also asked to attempt variations of the solved problems to help them understand the concepts better. Key features of the book are:

- 1350+ solved problems in 2 volumes
- Concept building by problem solving
- IIT preparation with school education
- Topic and year-wise content arrangement
- Promotes self learning
- Quality typesetting and figures

The readers can use the book as a readily available mentor for providing hints or complete solutions as per their needs.

7.2: About Contents

The volume 1 of the book covers three parts: Mechanics, Waves, and Optics. The list of chapters in this volume are:

- 1. Units and Measurements
- 2. Rest and Motion: Kinematics
- 3. Newton's Laws of Motion
- 4. Friction
- 5. Circular Motion
- 6. Work and Energy
- 7. Centre of Mass, Linear Momentum, Collision
- 8. Rotational Mechanics
- 9. Gravitation
- 10. Simple Harmonic Motion
- 11. Fluid Mechanics
- 12. Some Mechanical Properties of Matter
- 13. Wave Motion and Waves on a String
- 14. Sound Waves
- 15. Light Waves
- 16. Geometrical Optics
- 17. Optical Instruments
- 18. Dispersion and Spectra
- 19. Photometry

The volume 2 of the book covers three parts: Thermodynamics, Electromagnetism, and Modern Physics. The list of chapters in this volume are:

- 20. Heat and Temperature
- 21. Kinetic Theory of Gases
- 22. Calorimetry
- 23. Laws of Thermodynamics
- 24. Specific Heat Capacities of Gases
- 25. Heat Transfer
- 26. Electric Field and Potential
- 27. Gauss's Law
- 28. Capacitors
- 29. Electric Current in Conductors
- 30. Thermal and Chemical Effects of Electric Current
- 31. Magnetic Field
- 32. Magnetic Field due to a Current
- 33. Permanent Magnets

- 34. Electromagnetic Induction
- 35. Alternating Current
- 36. Electromagnetic Waves
- 37. Electric Current through Gases
- 38. Photoelectric Effect and Wave-Particle Duality
- 39. Bohr's Model and Physics of the Atom
- 40. X-rays
- 41. Semiconductors and Semiconductor Devices
- 42. The Nucleus

7.3: About Authors

Jitender Singh is working as a Scientist in DRDO. He has a strong academic background with Integrated M. Sc. (5 years) in Physics from IIT Kanpur and M. Tech. in Computational Science from IISc Bangalore. He is All India Rank 1 in GATE and loves to solve physics problems. He is a member of Prof. H.C. Verma's team which is dedicated to improve the quality of physics education in the country.

Shraddhesh Chaturvedi holds a degree in Integrated M. Sc. (5 years) in Physics from IIT Kanpur. He is passionate about problem solving in physics and enhancing the quality of texts available to Indian students. His career spans many industries where he has contributed with his knowledge of physics and mathematics. An avid reader and a keen thinker, his philosophical writings are a joy to read.

7.4: Where to Buy

Please visit www.concepts-of-physics.com to find links to the books page on Amazon. This website also give additional information about the book.



